PMXSPEC[®] DESIGNED FOR THE MODERN WORKER





Experience unparalleled comfort with our lightweight safety glasses. Customizable fit, enhanced field of vision, superior protection, anti-fog clarity, and stylish design. Built tough to meet high impact standards and shield from UV rays. Ideal for long hours on the job.



FEATURES

Unparalleled Comfort: Experience the ultimate comfort with our lightweight safety glasses, ideal for long hours on the job

Customized Fit: The adjustable soft rubber nose piece and non-slip temple grips ensure a secure and comfortable fit in all conditions

Enhanced Field of Vision: The panoramic wraparound lens offers an extended field of vision, crucial for safety in busy work environments

Superior Protection: The large lens provides effective protection from wind, dust, and debris, ensuring eyes are protected at all times

Anti-Fog Clarity: The lens is treated with anti-fog properties to guarantee fog-free clarity, even in extreme conditions

Stylish and Functional: The lens is mirrored and beveled, reducing glare and adding a unique aesthetic appeal

Built Tough: Meets ANSI/ISEA Z87.1-2020, See certified for CAN/CSA Z94.3-20 high impact standards and shields eyes from harmful UV rays



SB11265ST



SBL11257ST

PYRAMEX[®] N M - A O A * M P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM

PMXSPEC[®] DESIGNED FOR THE MODERN WORKER

Experience unparalleled comfort with our lightweight safety glasses. Customizable fit, enhanced field of vision, superior protection, anti-fog clarity, and stylish design. Built tough to meet high impact standards and shield from UV rays. Ideal for long hours on the job.



Overall Length (lens - tip): 153

Overall Width (hinge - hinge):

mm

150 mm

VARIATIONS



MATERIALS

Lens	Temples	Temple Tip	Nose Piece	Hinge
Polycarbonate	Polycarbonate	Rubber	Rubber	Polycarbonate

MARKINGS

Part No.	Lens Marking	Temple Marking	Lens Marking Symbols	Temple Marking Symbols	Measurements
SB11265ST	P + S	P Z87 + / P c SEI Z94.3	P: Manufacturer's Mark	P: Manufacturer's Mark	Weight: 34 gm
SB11295ST	P + S	P Z87 + / P c SEI Z94.3	+: High Impact	Z87: ANSI/ISEA Z87.1-2020 Standard for Eye and Face Protection Devices	Lens Base: 6.5 base
SBL11257ST P + S	P + S	P Z87 + / P c SEI Z94.3	S: Special Purpose		Lens Size Diagonal: 147 mm
			+: High Impact	Lens Size Vertical: 56 mm	
				₂ 55 Z94.3: Certified for CAN/CSA Z94.3-20 Standard for Eye and Face	Lens Thickness: 2 mm

Protection Devices

Product markings may vary // Updated as of 06.24 $\,$

PYRAMEX[®] ♥ ₩ ~ ∧ 0 ↔ ☆ △ P 800.736.8673 // F 901.861.4967 // W PYRAMEX.COM